



# FT SYNTHETICS

Gatorshield is a non-breathable vapor Barrier



**GRIPSPOT®**  
Slip resistant  
walking surface

- ✓ **Easy To Use**
- ✓ **No Stains**
- ✓ **Slip Resistant**
- ✓ **Durable**
- ✓ **Re-Useable**
- ✓ **100% Recyclable**

Gatorshield is a high strength synthetic floor protection product designed for use in new construction, renovations and for moving projects. Keeps floors clean and protected.

# FEATURES AND BENEFITS:



## Absorbent

Absorbs spills without leaking through and risking stained floors.

## Safe

GRIPSPOT slip resistant walking surface.

## Durable

Industry leading tear and tensile strength to withstand the high traffic demands for use on commercial, industrial and residential projects.

## Easy to Use

Cold weather flexible to -40°F, high temperature stable to 240°F.

## Multi-Surface

Specifically designed to protect wood, tile, vinyl, laminate, hardwood, and **CURED** concrete flooring.

## Cost Effective

Unlike paper products Gatorshield is designed for multiple time use. Simply wipe or vacuum surface and roll up for easy removal and relocation.

## Shock Absorbent

Protects floors from construction damage caused by; tools, foot traffic, dolly's, wheelbarrows, ladders, etc...

**\*Custom logo printing available**



Description	Specification
Roll Weight (lbs)	14.25 lbs
# of Rolls Per Pallet	49
Roll Dimensions - W x L	38 in x 100 ft
Roll Coverage (sq ft)	317 sq ft
Thickness (mils) ASTM D1970	30 mils (3 times more than Rosin Paper)
Tensile Strength (lbs) ASTM D5034	Machine Direction: 160 lbs
	Cross Direction: 150 lbs
Elongation (%) ASTM D5034	Machine Direction: 25%
	Cross Direction: 25%
Tear Strength (lbs/in) ASTM D4533	Machine Direction: 35 lbs
	Cross Direction: 30 lbs
Cold weather flexibility	-40°F (-40°C)
High temperature stability	240°F (115°C)
Water Absorbency	0.3 oz / yd <sup>2</sup> <1 min

Values are typical data and not limiting specifications. All values ± 10%.

**FT Synthetics Inc.**

5690 - 268 Street, Langley BC Canada V4W 3X4

Ph: 604-594-3439 Toll Free: 844-353-9839